Revised on 08/08/2023

· Product identifier

· Trade name: <u>ALUBE-500</u>

· Article number: 1309

- · Details of the supplier of the safety data sheet
- · Manufacturer:

ATCO International 1401 Barclay Circle

Marietta, Georgia 30060 USA www.atcointernational.com

- · Information department: Technical Services
- · Emergency telephone number:: +1 (800) 255-3924 (24-hours, ChemTel)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

1317-33-5 molybdenum disulphide

0.5-1.5%

4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.

(Contd. on page 2)

Revised on 08/08/2023

Trade name: ALUBE-500

(Contd. of page 1)

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· <i>PAC-1</i> :		
471-34-1	calcium carbonate, precipitated	45 mg/m^3
1317-33-5	molybdenum disulphide	50 mg/m^3
108-32-7	propylene carbonate	34 mg/m^3
14808-60-7	Quartz (SiO2)	0.075 mg/m
· PAC-2:		
471-34-1	calcium carbonate, precipitated	210 mg/m
1317-33-5	molybdenum disulphide	260 mg/m
108-32-7	propylene carbonate	370 mg/m
14808-60-7	Quartz (SiO2)	33 mg/m³
· <i>PAC-3</i> :		
471-34-1	calcium carbonate, precipitated	1,300 mg/m
1317-33-5	molybdenum disulphide	1,600 mg/m
108-32-7	propylene carbonate	2,200 mg/m
14808-60-7	Quartz (SiO2)	200 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.

(Contd. on page 3)

Revised on 08/08/2023

Trade name: ALUBE-500

(Contd. of page 2)

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Semi-Solid Color: Grev

Odor: Petroleum-like · Odor threshold: Not determined. Not determined.

· Change in condition

Melting point/Melting range: Undetermined. 338 °C (640.4 °F) Boiling point/Boiling range:

255 °C (491 °F) · Flash point:

· Flammability (solid, gaseous): Not applicable. · Ignition temperature: 190 °C (374 °F)

(Contd. on page 4)

Reviewed on 08/08/2023

Trade name: ALUBE-500

	(Contd. of page	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	0 hPa	
Density at 20 °C (68 °F):	1.15316-1.19412 g/cm³ (9.62312-9.96493 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	e r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents: 0.9 %		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	19.2 %	
ther information No further relevant information available.		

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 5)

Reviewed on 08/08/2023

Trade name: ALUBE-500

· Additional toxicological information:

(Contd. of page 3)

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Carcinogenic categories

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

K

· OSHA-Ca (Occupational Safety & Health Administration): (Substances not listed)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- *Uncleaned packagings:*
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name		
DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	

(Contd. on page 6)

Reviewed on 08/08/2023

Trade name: ALUBE-500

Contd. of page 3)

• Environmental hazards:
• Marine pollutant:
No

• Special precautions for user
Not applicable.

• Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code
Not applicable.

• UN "Model Regulation":
not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

0.087%

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· TLV (Threshold Limit Value)

14808-60-7 Quartz (SiO2)

A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

- GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

HS

Reviewed on 08/08/2023

Trade name: ALUBE-500

(Contd. of page 3)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Services
- · Date of preparation / last revision 08/08/2023 / Revision 1.0
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

* Data compared to the previous version altered.

... END of SDS...

US