

Product Data

PREP-A-LUBE

Penetrating Non-Melt Red Spray Grease

PREP-A-LUBE red non-melt spray grease penetrates and lubricates difficult to reach application areas (wire ropes, cables, rollers, etc.) and cures to an extra heavy-duty grease that holds up under wide temperature ranges and extreme pressure. PREP-A-LUBE will not run or liquefy under heat, and it will not be washed away by water or steam. It lubricates in the presence of water and withstands heavy loads and high impact.

- ✓ Does Not Contain Any CFC's or 1,1,1 Trichloroethane
- ✓ Operates Under Temperatures From -40°F to +500°F
- ✓ Penetrates Deeply Into Difficult To Lubricate Surfaces
- ✓ Wash Out Resistant
- ✓ Extreme Pressure Resistant



...setting performance
standards worldwide...

APPLICATIONS

PREP-A-LUBE is a non-melt bentone red spray grease with penetrating action. It actually removes grit, grime and old grease when applied. It then cures to a thick, non-melt, pressure-resistant coating that protects and lubricates equipment. PREP-A-LUBE also resists acids, oxidation and dirt, and it prevents rust and corrosion.

PREP-A-LUBE is recommended for wire rope, conveyor chains, chassis, linkages, draglines, water meters, valves, fittings, threads, pulleys, fork lifts, rollers, presses and anywhere a penetrating grease can be used.

DIRECTIONS

Spray first up close to flush off old grease and dirt build-up. Then spray a light film on the surface to be lubricated or protected. Material will start forming into grease in minutes. Allow 15 to 20 minutes for product to fully cure.

TECHNICAL DATA

Composition:	Non-melt bentone spray grease
Toxicity:	25 ppm OSHA TLV
Flammability:	Extremely Flammable as per USA Flame Projection Test
Water Resistant:	Yes
Rust Resistant:	Yes
Color:	Red
VOC Content:	48.5%



...setting performance
standards worldwide...

C-13/PC-5400/0711