

RE-MARKABLE

White Traffic Marking Paint

RE-MARKABLE White Traffic Marking Paint is a long-lasting striping paint that is ideal for use on concrete, blacktop and most other surfaces where a sharp, well-defined marking line is required. RE-MARKABLE may be used in ATCO's Traffic Marking Machine to produce 2" to 4" inch wide marking stripes. It dries to the touch in 15 minutes and is traffic ready in 60 minutes. RE-MARKABLE is V.O.C. compliant, and one can will stripe 250 linear feet.

- ✓ Makes 2" to 4" Wide Stripes
- ✓ Traffic Ready in 60 Minutes
- ✓ One Can of RE-MARKABLE Will Stripe Approximately 250 Linear Feet
- ✓ V.O.C. Compliant
- ✓ Traffic White Color



*...setting performance
standards worldwide...*

APPLICATIONS

RE-MARKABLE White Traffic Marking Paint is a long-lasting striping paint that is traffic ready in 60 minutes. RE-MARKABLE is specifically designed for use on concrete, blacktop and many other surfaces. It eliminates asphalt bleed-through and is ideal for use on parking lots, driveways, recreational facility surfaces and other areas where a traffic marking paint that produces sharp, well-defined lines is needed. When used in ATCO's Traffic Marking Machine, RE-MARKABLE will make 2"-4" wide stripes, and one can will stripe 250 Linear Feet. RE-MARKABLE is designed to be used in ATCO's Traffic Marking Machine, but because of its universal spray head, it can be used in many different marking machines.

DIRECTIONS

1. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Turn can upside down and place into holder of the Traffic Marking Machine. MAKE SURE THAT SPRAYHEAD FITS PROPERLY INTO HOLE. The long side of the sprayhead must be parallel to the axle. By adjusting the can platform up or down, stripes approximately 3 to 5 inches wide can be applied.
4. Squeeze trigger to activate spray. To avoid any possible "build-up" of paint when starting, it is suggested that the machine be in motion when passing over the starting point.
5. If clogging develops, take the can out of the marking machine. Remove sprayhead from can and clean orifice in sprayhead. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
6. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

TECHNICAL DATA

Composition:	White traffic marking paint
Specific Gravity:	0.83
Flammability:	Flammable
Storage Temperature:	40-100°F
Application Temperature:	50-90°F
Dry Time:	To touch - 15 minutes; traffic ready - 60 minutes
Equipment:	ATCO's Traffic Marking Machine



...setting performance standards worldwide...

C-5/PC-5637/0611